



## Remote Controlled Power Switch



Part Number: CL-POW-10

### PRODUCT FEATURES

- Compatible to all ClickOn remote controls
- Remote control of high wattage loads
- Override button for local on/off switching
- Operating voltage: 220V to 240VAC
- High current relay output.
- Maximum load @ 230VAC:
  - \* General purpose resistive: 2000W (8.7A)
  - \* Incandescent / Halogen lights: 2000W
  - \* Ballast (fluorescent lights): 2000W
  - \* Motor: 2.7HP (2000W)
  - \* Low voltage lighting transformers: 2000W
- User friendly programming
- Two modes of operation:
  - \* Mode 1: Manual on/off switching disabled
  - \* Mode 2: Manual on/off switching enabled. In this mode the power switch can be switched on/off by a wall switch connected in series with the power switch. It is achieved by switching the wall switch to the off position and immediately back on again.
- External pushbutton switch input
- Data output to connect slave units
- Memory capacity: 24 ClickOn remote control channels
- Power failure memory
- LED indicator: Green when OFF, Red when ON
- Connections: via 200mm wires
  - \* Live in: Brown
  - \* Neutral: Blue
  - \* Live out (load): Red
- \* Range: 30 to 100m
- \* Dimensions: 75 x 54 x 37mm
- \* Available in long range model (range up to 150m): Part Number CL-POW-10LR
- \* Available in a slave model (no rf receiver); part number CL-POW-10SL for close proximity mounting to a master